

DOME OPTIC SPLICE CLOSURE

Specification No. GJS-JKDH1001-120

FIBER OPTIC SPLICE CLOSURE



Product Introduction

GJS — JKDH1001-120 Cap type series of a cable connector box. Products can be used in overhead, holding pole, wall and buried installation; good seal performance of the products, simple operation of installation and wide range; in the optical fiber transmission process, the products are through connection, function difference and the male mentioned sealing joint protection.

Product Description

- 1. IP protection level can reach IP68.
- 2. Can be installed 1 x "PLC shunt and 2 x for PLC shunt.
- 3. With four small round into the cable hole and a large oval into line hole.
- 4. Joint box shell by vulcanized rubber for seal.
- 5. Cable in and out of holes are hot shrinkage seal.
- 6. BOX DIMENSION: L=150mm H=370mm Weight = 1.8 kg

Characteristics

- convenient to increase or decrease the size according to the capacity of the melt flange quantity.
- 2. Three Settings prevent cable is external pulled off
- 3. Molten flange space is big, easy to maintain and storage of optical fiber
- 4. Temperature range to use at $^{\circ}$ C to + 65 $^{\circ}$ C
- 5. Easy to repeat, open, no tools are required, waterproof, prevent gas leakage, flame retardant
- 6. Set vertical and horizontal design characteristics
- 7. SGS ROHS testing the authentication
- 8. Suitable for aerial, buried, pipe use



Website: www.jk-dynamic.com Office Tel: +662-159-8014 | Fax: +662-159-8041



Item	Dimension (mm)	In/o ut port s	Max. cable diameter (mm)	Max. capacity per tray	Disc numbe r	Max capacity (bunchy fiber)	Seal method
GJS-JKDH1001- 120	H=370 x150 mm	5	4 of Φ16	24cores	1-6	144cores	Heat- shrink seal

Main components

no.	Name of components	quantity	usage	remark s
1	FOSC Cover	1 piece	Comprehensive protection joint	
2	Fuse fiber disc	According to the request	Fixed, save fiber and protect optical fiber hot melt pipe	
3	base	1 unit	Fixed inside and outside structure	
4	Plastic hoop	1 set	Fixed base and shell	
5	Type O sealing ring	1 set	Used to seal base and shell seal	
6	External Grounding	1 set		

Website: www.jk-dynamic.com Office Tel: +662-159-8014 | Fax: +662-159-8041



Optional accessories: valve, earthing device, optical splitter, adapter, pigtail, wire jumper

Accessories: specification, cable protection heat shrinkable tube, fiber heat shrinkable, buffer tube, earthing wire, nylon tie, sand paper, Differences card, labeling paper, desiccant, tin foil, insulating tape.







Website: www.jk-dynamic.com Office Tel: +662-159-8014 | Fax: +662-159-8041